

Ultra Low Pressure RO Membrane Element 2540

APPLICATIONS

- Brackish water, groundwater, surface water, tap water treatment etc.
- Liquid concentration, sewage wastewater and reclaimed water recycle etc.
- Feed TDS below 5000mg/L.
- Production water supply system for electronics, power, steel & iron, pharmacy, thermoelectric , petrochemical, coal to chemicals etc.

BENEFITS

- High Rejection Rate and Strong Stability
- Economical and Applicability

SPECIFICATIONS

Model	Active Area ft2(m2)	Feed Spacer Thickness(mil)	Permeate Flow Rate GPD(m3/d)	Stabilized Salt Rejection (%)
MBR-2540 ULP	27 (2.5)	28	750 (2.8)	99.20

STANDARD TEST CONDITION

Solution	Temperature (°C)	pH	Operating Pressure psi(MPa)	Recovery (%)
1500mg/L NaCl	25	7.5-8.0	150 (1.03)	15

Individual flow rate may vary ±15%

ELEMENT DIMENSIONS AND OPERATING LIMITS

Model	Active Area ft2(m2)		Feed Spacer Thickness(mil)		Permeate Flow Rate GPD(m3/d)	
	inch	mm	inch	mm	inch	mm
MBR-2540 ULP	40	1016	7.9	201	1.12	28.5




+55 32 99112-2628




info@membras.com

Ultra Low Pressure RO Membrane Element 2540



Maximum Operating Pressure	600psi(4. 14MPa)
Maximum Operating Temperature	45°C
Maximum Feed Silt Density Index	5.0
Free Chlorine Tolerance	0. 1mg/L
pH Range,Continuous Operation	3- 10
pH Range,Short-Term Cleaning	1- 13
Maximum Element Pressure Drop	15psi(0. 1MPa)



DIMENSIONS			
A mm (in.)	B mm (in.)	C mm (in.)	D mm (in.)
1,016 (40)	200 (7.9)	28.6 (1.125)	16 (.35)

The dimensional information is indicative and is provided as a reference. Please contact us for detailed technical specifications.